



A part of your family....

Horizontal Openwell

*Performance At Rated Voltage i.e. 240v And 415v, 50Hz, Ac Supply.

Horizontal Openwell (V8 Eco Series Casting Body)

MODEL NO.	H.P.	OUTLET	PHASE	HEAD IN METERS.												
					5	10	15	20	25	27	30	33	35	40	45	
KMP-490	3.00	2.5x2	3ø	DISCHARGE IN L.P.M.	690	652	579	533	373	283	67	S.-31M				
KMP-491	3.00	2.5x2.5	3ø		771	732	600	550	337	S.O-27M						
KMP-492	5.00	2.5x2	3ø		705	675	641	580	495	408	305	215	S.O37M			
KMP-493	5.00	2.5x2.5	3ø		975	958	880	775	588	550	372	S.O34M				
KMP-494	6.00	2.5x2	3ø		900	857	735	641	514	465	380	283	198	S.O42M		
KMP-495	6.00	2.5x2.5	3ø		1133	1100	957	809	596	549	490	240	S.O36M			
KMP-496	7.50	2.5x2	3ø		955	930	910	900	880	850	815	795	730	580	375	S.O50M
KMP-497	7.50	2.5x2.5	3ø		1253	1218	1078	927	717	664	612	369	S.O35M			

Horizontal Openwell (Single / Three Phase)

MODEL NO.	H.P.	TYPE	OUTLET	PHASE	HEAD IN METERS											
						05	10	15	20	25	27	30	33	35	40	45
KMP-66	0.50	V/5-SS	1 x 1	1ø	DISCHARGE IN L.P.M.	145	130	65	S.O-18M							
KMP-67	1.00	V/7-SS	1 x 1	1ø		245	218	195	155	102	31	S.O-28M				
KMP-68	1.50	V/7-SS	2 x 1.5	1ø		435	375	310	230	120	S.O-26M					
KMP-69	2.00	V/7-SS	2 x 2	1ø		456	430	371	310	170	108	S.O-29M				
KMP-70	3.00	V/7-SS	2.5 x 2	1ø		578	541	491	408	312	260	122	45	S.O-34M		
KMP-71	5.00	V/7-SS	2.5 x 2	1ø		745	732	686	604	515	486	384	271	185	S.O-37M	

MODEL NO.	H.P./ STAGE	TYPE	OUTLET	PHASE	HEAD IN METERS												
						05	10	15	20	25	27	30	33	35	40	45	
KMP-71A	0.50	V/5-SS	1 x 1	1ø	DISCHARGE IN L.P.M.	120	105	87	55	S.O-25M							
KMP-71B	1.00	V/5-SS	1 x 1	1ø / 3ø		179	166	145	118	74	51	35	S.O-32M				
KMP-71C	2/2	V/7-SS	1.5 x 1.5	1ø / 3ø		403	388	365	341	326	314	296	240	205	112	S.O-46M	
BELOW ALL CR MODELS						BELOW ALL CR MODELS											
KMP-71D	2.00	V/7-SS	2 x 2	1ø		456	430	371	310	170	108	S.O-29m					
KMP-71E	3.00	V/7-SS	2.5 x 2	1ø		578	541	491	408	312	260	122	45	S.O-34m			
KMP-71F	5.00	V/7-SS	2.5 x 2	1ø		745	732	686	604	515	486	384	271	185	S.O-37m		



A part of your family....

Horizontal Openwell

Super Deluxe (Casting Body V/7 Openwell) (Single / Three Phase)

MODEL NO.	H.P./ STAGE	TYPE	OUTLET	PHASE	HEAD IN METERS								
						05	10	15	20	23	25	27	30
BELOW AR MODELS					DISCHARGE IN L.P.M.	BELOW AR MODELS							
KMP-399	2.0	V/7-CI	2 x 2	1ø		593	548	474	340	220	128	0	-
KMP-400	3.0	V/7-CI	2.5 x 2	1ø		845	723	620	529	465	357	300	-
KMP-401	5.0	V/7-CI	2.5 x 2	1ø		881	755	675	608	495	425	347	160
BELOW CR MODELS						BELOW CR MODELS							
KMP-402	2.00	V/7-CI	2 x 2	1ø		593	548	474	340	220	128	0	-
KMP-403	3.00	V/7-CI	2.5 x 2	1ø		845	723	620	529	465	357	300	-
KMP-404	5.00	V/7-CI	2.5 x 2	1ø		881	755	675	608	495	425	347	160
BELOW AR MODELS						BELOW AR MODELS							
KMP-405	2.00	V/7-CI	2 x 2	3ø		593	548	474	340	220	128	0	-
KMP-406	3.00	V/7-CI	2.5 x 2	3ø		845	723	620	529	465	357	300	-
KMP-407	5.00	V/7-CI	2.5 x 2	3ø		881	755	675	608	495	425	347	160
BELOW CR MODELS						BELOW CR MODELS							
KMP-408	2.00	V/7-CI	2 x 2	3ø		593	548	474	340	220	128	0	-
KMP-409	3.00	V/7-CI	2.5 x 2	3ø		845	723	620	529	465	357	300	-
KMP-409A	5.00	V/7-CI	2.5 x 2	3ø		881	755	675	608	495	425	347	160

MODEL NO.	H.P.	TYPE	OUTLET	PHASE	HEAD IN METERS											
					5	10	15	20	25	27	30	33	35	40	45	
KMP-72	1.00	V/7-SS	1x 1	3ø	DISCHARGE IN L.P.M.	245	218	195	155	102	31	S.O-28M				
KMP-73	1.50	V/7-SS	2 x 1.5	3ø		435	375	310	230	120	S.O-26M					
KMP-74	2.00	V/7-SS	2 x 2	3ø		456	430	371	310	170	108	S.O-29M				
KMP-75	3.00	V/7-SS	2.5 x 2	3ø		578	541	491	408	312	206	122	45	S.O-34M		
KMP-76	5.00	V/7-SS	2.5 x 2	3ø		745	732	686	604	515	486	384	271	185	S.O-37M	
KMP-77	3.00	V/9-CI	2.5 x 2	3ø		725	687	614	568	408	318	102	S.O-31.5			
KMP-78	3.00	V/9-CI	2.5 x 2.5	3ø		816	777	635	585	372	S.O-27M					
KMP-79	3.00	V/9-CI	3 x 2.5	3ø		925	832	741	330	S.O-23M						
KMP-80	5.00	V/9-CI	2.5 x 2	3ø		848	812	760	707	604	580	458	394	305	S.O-39M	
KMP-81	5.00	V/9-CI	2.5 x 2.5	3ø		935	895	825	762	635	510	260	S.O-31M			
KMP-82	5.00	V/9-CI	3 x 2.5	3ø		1219	1125	1070	870	S.O-24M						
KMP-83	6.00	V/9-CI	2.5 x 2	3ø		1025	982	860	766	639	590	505	408	323	59	S.O-42
KMP-84	6.00	V/9-CI	2.5 x 2.5	3ø		1248	1215	1072	924	711	664	605	S.O-33M			
KMP-85	6.00	V/9-CI	3 x 2.5	3ø		1345	1310	1193	1077	843	407	S.O-28M				
KMP-86	7.50	V/9-CI	2.5 x 2	3ø		1074	1041	905	840	718	665	615	508	412	382	²²⁴ S.O -49
KMP-87	7.50	V/9-CI	2.5 x 2.5	3ø		1308	1273	1133	982	772	719	667	424	S.O-35M		
KMP-88	7.50	V/9-CI	3 x 2.5	3ø		1410	1365	1259	1140	908	775	240	S.O-31M			



A part of your family....

Horizontal Openwell

Performance At Rated Voltage i.e. 240v And 415v, 50Hz, Ac Supply.

MODEL NO.	H.P.	TYPE	OUTLET	PHASE	HEAD IN MEETERS						
KMP-243	10.00	V9-MS	2.5/2	3ø	DISCHARGE IN L.P.M.	38/700	44/620	46/480	52/360	54/300	56/270
KMP-244	10.00	V9-MS	3/2.2	3ø		27/930	30/830	33/750	35/640	38/500	-
KMP-245	10.00	V9-MS	4/4	3ø		20/1260	23/1450	25/1220	28/900	-	-
KMP-246	10.00	V9-MS	5/5	3ø		4/3200	6/3000	8/2700	10/2400	16/950	-
KMP-247	13.00	V9-MS	2.5/2	3ø		45/580	47/550	52/470	54/420	56/380	-
KMP-248	13.00	V9-MS	3/2.5	3ø		33/1050	35/870	38/760	40/700	43/580	-
KMP-249	13.00	V9-MS	4/4	3ø		20/1750	23/1600	25/1420	28/1150	30/950	-
KMP-250	13.00	V9-MS	5/5	3ø		4/3450	6/3250	8/3000	10/2750	16/2000	-
KMP-251	15.00	V9-MS	2.5/2	3ø		45/640	47/585	52/535	54/480	56/410	58/345
KMP-252	15.00	V9-MS	3/2.5	3ø		32/1375	35/1175	38/1075	40/850	42/590	-
KMP-253	15.00	V9-MS	4/4	3ø		20/1855	22/1760	25/1600	28/1500	30/1230	-
KMP-254	15.00	V9-MS	5/5	3ø		8/3430	12/3160	16/2970	18/2690	20/2110	-